

L1+

4K UHD Ultra Short Throw LED Home Projector









- The most compact, economical, true 4K UHD visual experience UST Projector - 8.3 million onscreen pixels, HDR and HLG compatible
- Built with 4LED Technology Enhanced contrast, brightness, color and up to 30,000 hours long lifespan.
- Designed with the environment in mind Built with 50% PCR recycled materials
- Enhanced gaming mode Low lag gaming



The stylish L1+ is Optoma's most compact, power saving and eco-friendly 4K Ultra-short throw to date.

Designed for environmental sustainability, the L1 Smart maintains brightness and colour saturation for longer with energy-saving LED technology for up to 30,000 hours of maintenance free projection. It's compact and lightweight chassis also features 50% PCR recycled materials in an effort to reduce Optoma's logistical impact on the environment as well as our overall carbon footprint.

Specifications

Gross weight

Net weight

Specifications	
Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	2,500 lumens
Brightness (HK)	2,500
Contrast ratio	1,800,000:1
Native aspect ratio	16:9
Keystone correction - horizontal	-10~+10°
Keystone correction - vertical	-10~+10°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 145Khz
Vertical scan rate	24 ~ 240Hz
Screen size	1.52m ~ 3.05m (60" ~ 120") diagonal
Lamp info	
Light source type	LED
LED life	30,000 hours
Optical	
Throw ratio	0.25:1
Projection distance	0.47m - 0.59m
Focal length	2.63mm
Native offset	126%
Connectivity	
Connections	Inputs 3 x HDMI 2.0
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x S/PDIF, 1 x Micro-USB
General	
Noise level (typical)	25dB
Noise level (max)	28dB
3D compatibility	Yes (DLP 3D)
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
360° operation	Yes
Operating conditions	0~40°C/32°F~104°F, max altitude 10,000ft, max humidity 85%
Remote control	Card style
Speaker count	2
Watts per speaker	10W
In the box	1x Remote 1x HAKO Mini ATV Dongle
Power	
Power supply	100V ~ 240V, 50-60Hz
Power consumption (min)	145W
Power consumption (max)	165W
Weight and dimensions	
Dimensions (W x D x H)	400 x 316 x 112.8
	= 0.1

7.8 kg 5.1 kg



