PHILIPS

SmartMeeting

4K UHD presentation

Voice tacking 5x HD zoom Smart framing 120° horizontal view Built-in voice processor





- Voice tracking: The built-in 6-mic array realizes the voice tracking function and tracks each speaker in real time, allowing remote participants to break the limitation of distance and have an immersive and face-to-face experience.
- Built-in speakers: Built-in high-quality dual-speaker speakers ensure that every participant can hear the distant sound clearly and provide a unique remote experience.
- Intelligent framing: built-in face detection algorithm, automatically detect participants, and provide ideal framing.
- Ultra HD: Using 8 million high-quality CMOS image sensors, it can capture 4K ultra-high-definition images, present clear and lifelike ultra-high-definition videos, vividly show the expressions and movements of characters, and provide super-class definition and resolution image quality.

• Large viewing angle lens without distortion: With a 120° large viewing angle without distortion lens, there is no need to adjust the lens position, all participants have a panoramic view, and easily cover every corner of the conference room.

 Low noise and high signal-to-noise ratio: The low-noise CMOS effectively ensures the high signal-to-noise ratio of the picture. Adopt advanced 2D and 3D noise reduction technology to further reduce noise while ensuring image clarity.

Specifications

- Model: PHILIPS PSE0800
- Image Sensor: 1/2.8-inch, 8-megapixel CMOS
- Zoom: 5x Zoom
- Video output: Up to 4K image output
- Microphone arrangement: Ring
- Al intelligent framing: Automatic group framing and speaker tracking
- Optical lens: 116°(D)/107.2°(H)/74.1°(V)
- Video resolution: 4K/30 backward compatible
- PTZ: EPTZ
- Digital noise reduction: 2D & 3D
- BLC: support
- Signal to noise ratio: ≥55dB
- Microphone type: 6 digital array microphones
- Pickup distance: 6 meters
- Audio processing: AEC & AGC & ANS & Sound Source Localization
- Speaker: 2*7W
- Remote control: Infrared remote control
- USB interface: 1*USB3.0 (compatible with USB2.0), B port
- Audio port: Reserve 1*3.5mm linear input
- Power interface: HEC3800 power socket (DC12V)
- Wall bracket: Standard wall mount bracket



Marketing Office

1101, 11th Floor, Mehdi Tower, SMCHS, Shahrah-e-Faisal, Karachi. T: +92 (21) 34325512-14 F: +92 (21) 34325517 E: info@kbse.com.pk

Lahore

65-Garden Block, New Garden Town, Lahore. T: +92 (42) 35851065-6 F: +92 (42) 35840965 E: Ihr@kbse.com.pk

Islamabad

H-1566, Street 54, Phase III, Bahria Town, Islamabad. T: +92 (51) 5733303 T: +92 (51) 5733470 E: isb@kbse.com.pk

Multan

17-A, Oppt. Excise Office Main Gate Near MDA Chowk, Lodhi Colony Road, Multan. T: +92 (61) 4422037 E: mux@kbse.com.pk