

Solid Performance with Energy Saving



color and image guarantees ensure hassle free, long lasting projection. The Eco+ technology brings together superb performance, efficient lamp life and energy saving features that are easy to use and save both time and money. Additionally, both presenters and viewers will be beneficial from the 3D capability, which elaborates the presentation by offering 3D contents.

Optoma S2010 Projector offers a better solution for

all your needs regardless of the venue. Featuring 3,000 ANSI lumens and 15,000:1 contrast ratio ensure remarkable performance with quality images. S2010 provides the most compelling visual experience within the filter-free, low maintenance design and the unique

Features

- **3,000 ANSI lumens**
- **15,000:1 high contrast ratio**
- **Dust Filter Design**
- **3D Compatibility**
- **Up to 6,500h lamp life and 70% energy saving(Eco+ Mode)**
- **Individual color adjustment (R,G,B Gain/Bios)**



S2010

High contrast ratio for sharp images

This measurement technique includes a reproducible procedure that can be used to compare the performance of projectors using different display technologies. With an ANSI contrast ratio significantly higher than many LCD based projectors, S2010 produce a stunning 15,000:1 contrast ratio for pin sharp, crystal clear images. Crisper whites and ultra rich blacks bring the picture to life.

BrilliantColor™-II

BrilliantColor™ allows the usage of a more advanced image processing algorithm and enables the usage of more colors on the color wheel, than the standard Red, Green, Blue and White segments. New BrilliantColor™-II technology enables higher brightness levels by boosting mid-tone colors, resulting in more vibrant, precisely accurate colors projected on the screen.

6 Segments Color Wheel

Produces 3X Color Wheel Rotation Speed projectors support PAL video signals in movie mode, which operate at only 50 Hz frequency. Under this low frequency, projector increases the speed of the color wheel rotation from 2X (7200 rpm) to 3X (10800 rpm) resulting in consistent colors and seamless video playback.

Input / Output Connections

- 01. AUDIO IN
- 02. S-VIDEO
- 03. VGA1/YPbPr
- 04. VGA-OUT
- 05. RS232C
- 06. SERVICE
- 07. KENSINGTON™ LOCK
- 08. AUDIO OUT
- 09. VIDEO
- 10. VGA2/YPbPr



Eco+ Technology

Eco+ technology from Optoma increases our commitment to reduce the impact we all make on the environment. Eco+ technology reduces the power consumption to as little as 30%. This intelligent feature also has a positive effect on the lamp life, increasing it up to 70% while lowering the total cost of ownership and reducing maintenance.

Longer lamp life

With Eco+ technology, the lamp life will be increased up to 6500 hours. It lowers the total cost of ownership and maintenance.

Greater lamp efficiency

This intelligent feature adjusts the brightness of the lamp by detecting darkness from the image, also has a positive effect on the lamp life; increasing it up to 70% while lowering the total cost of ownership and reducing maintenance.

Lower energy consumption

Set the projector in Eco+ mode and turn on the auto power off feature, enabling the <0.5W standby mode ensures the minimum energy consumption to 10% when the projector is not switched on.

Specification	S2010
Display Technology	TI DLP® technology / 0.55" SVGA DMD Chip
Native Resolution	Native: 800x600 (SVGA) Support Computer signal up to UXGA (1600x1200) 60Hz
Brightness / Contrast Ratio	3,000 ANSI Lumens / 15,000 :1
Display Colors	1073.4 million colors (10bit)
Projection Lens	F=2.51-2.69 ; f = 21.95-24.18 mm; 1.1x manual zoom / focus lens.
Image Size	30 to 300 inch
Projection Distance	1.2m -10m
Throw Ratio (projection distance / width)	1.97 - 2.17 :1
Digital Keystone Correction	±40° Vertical (system)
Aspect Ratio	4:3 Native, 16:9 Compatible
Scan Rate	Horizontal: 15.375-91.146 KHz, Vertical: 24-85 Hz (120Hz for 3D feature)
Computer Compatibility	UXGA, SXGA+, SXGA, SVGA, VGA Compression, VESA standards, PC & Macintosh compatible
Video Compatibility	HDTV(720p,1080i/p), SDTV(480i/p,576i/p), Full NTSC,PAL PAL-M,PAL-N,SECAM
Input / Output Connections	VGA in x 2, VGA Out x 1, S-Video x 1, Composite Video x 1, Audio Input x 2, Audio output x 1, RS-232 control interface x 1(9 Pin), USB Type B x 1
Uniformity	85 %
Speaker	2W x 1
Noise	31 dB (Bright mode) / 34 dB (within dust filter)
Lamp Type	190 watt user-replaceable lamp
Lamp Life	6500 Hrs (Eco mode) / 4500 Hrs(Bright mode)
Power Supply	Universal AC 100-240V ±10%, 50/60Hz
Dimensions(WxDxH) / Weight	316 x 224 x 124 mm / 2.2kg (4.85 lbs)

*Optoma reserves the right to change this brochure without prior notice, please refer to www.optoma.com for any change



*Optoma guarantees that in normal use, Optoma DLP® color quality will be indistinguishable from when new. Please note that worn lamps will give slight variance. Exclusions: (1) Guarantee is voided if the projector is subject to damage through mis-use. (2) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is particularly excessive (3) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other fault. Typical lamp life achieved through testing. Will vary according to operational use and environment conditions. Optoma guarantees that in normal use, the DLP® imager guarantee will retain quality for at least 5 years providing consistent pixel performance. Exclusions: (1) Guarantee is voided if the projector is subject to damage through mis-use. (2) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is particularly excessive. Copyright © 2013, Optoma Corporation. All other product names and company names used herein are for identifications purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments.