

## ZX350e Compact high brightness laser projector





- Bright XGA DuraCore laser projector 3700 lumens and IP6X certified
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- Compact for easy installation 1.1x zoom, 360degree and portrait projection
- External power supply More reliability, portability and energy efficiency



The ZX350e is one of Optoma's most compact and hassle-free XGA DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 3700-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.<sup>1</sup>

An added benefit, the ZX350e features an external power supply offering more reliability, portability and energy efficiency.

## **Specifications**

EAN: 5055387666375, Colour: W	
UPC: 796435 44 611 6, Colour: W	VIIILE
Display/image	DLP™
Display technology	
Resolution	XGA (1024x768)
Brightness	3,700 lumens
Contrast ratio	300,000:1
Contrast ratio - dynamic	2,000,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Displayable colors (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	20" ~ 300" diagonal
Lamp info	
_ight source type	Laser
_ASER life	30,000 hours
Optical	
Throw ratio	1.94:1 ~ 2.16:1
Projection distance	39.37" - 393.7"
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85 ~ 24.01
Native offset	115%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
General	22.17
Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
2D	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
3D	Full 3D
-	Security bar, Kensington Lock, Password protected interface
-	Security bar, Kensington Lock, Password protected interface
P rating	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
P rating	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
P rating	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
P rating	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
P rating DSD / display languages	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
P rating DSD / display languages 24/7 operation	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
P rating DSD / display languages 24/7 operation 360° operation	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes
P rating DSD / display languages 24/7 operation 360° operation Operating conditions	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnaimese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m
P rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style
P rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1
P rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1
P rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	<ul> <li>IP6X</li> <li>25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>O°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m</li> <li>Card style</li> <li>1</li> <li>15W</li> <li>AC power cord</li> </ul>
P rating DSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control
P rating DSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	<ul> <li>IP6X</li> <li>25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese</li> <li>Yes</li> <li>Yes</li> <li>Yes</li> <li>O°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m</li> <li>Card style</li> <li>1</li> <li>15W</li> <li>AC power cord</li> </ul>
P rating OSD / display languages 24/7 operation 360° operation Deperating conditions Remote control Speaker count Watts per speaker n the box	<ul> <li>IP6X</li> <li>25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese</li> <li>Yes</li> <li>Yes</li> <li>0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m</li> <li>Card style</li> <li>1</li> <li>15W</li> <li>AC power cord</li> <li>Remote control</li> <li>1x CR2025 battery</li> </ul>
P rating DSD / display languages 24/7 operation 360° operation Doperating conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models	<ul> <li>IP6X</li> <li>25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese</li> <li>Yes</li> <li>Yes</li> <li>O°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m</li> <li>Card style</li> <li>1</li> <li>15W</li> <li>AC power cord</li> <li>Remote control</li> <li>1 x CR2025 battery</li> <li>Basic user manual</li> </ul>
P rating DSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models Power	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Itatian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro
P rating DSD / display languages 24/7 operation 360° operation Departing conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models Power Power supply	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz
P rating DSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models Power Power supply Power consumption (standby)	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W
P rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min)	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W
P rating DSD / display languages 24/7 operation 360° operation Departing conditions Remote control Speaker count Watts per speaker n the box Dptional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W
P rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W
P rating DSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H)	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W 10.79" x 8.5" x 4.49"
Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) Gross weight Net weight	IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C - 40°C, Max. Humidity 85%, Max. Altitude 2500m Card style 1 15W AC power cord Remote control 1x CR2025 battery Basic user manual UHDCast Pro External power supply, 100V ~ 240V, 50-60Hz <0.5W 88W 139W







Copyright © 2023 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. <sup>1</sup> Based on the comparison of the 2023 Optoma mainstream laser projectors and its previous generation. <sup>2</sup> Comparison of 2023 Optoma mainstream laser projectors and its equivalent lamp-based counterparts. <sup>3</sup> Based on the packaging of 2023 Optoma laser projectors. 01062023092437